

"Creating A Cleaner World"

through



JUBILEE
Environmental Products, LLC

406 S. Boulder, Suite 820
Tulsa, OK 74103
918-587-3948 (P)
918-295-9903 (F)
www.jep14.com

JEP-14

EMULSION DEGREASER/CLEANER

PATENTED DESIGN FEATURES

- Positively Emulsifies Oily Soil — Saves Time and Labor
- Contains No Solvents or Caustic — Safer to Use
- Works on Any Oily Soil — Simplifies Training
- Contains Corrosion Inhibitors — Use in Autoscrubbers and Prevents Flash Rusting

PROFESSIONAL RECOMMENDATIONS

- Use this product regularly for best results
- **NOT** recommended for removal of baked-on or dried, hardened soils
- Use "grit" type brushes on autoscrubber to enhance cleaning on unfinished concrete and other industrial floors
- Overlap cleaning passes to assure uniform cleaning and "double scrub" when heavy soil is present
- When mop cleaning, change cleaning solution frequently to get peak performance
- **DO NOT** let mop rest in cleaning solution between uses

SURFACE SAFETY

- Safe on most surfaces found in industrial settings
- Before cleaning aluminum, brass, copper or other non-ferrous metals, check for safety. If metal bubbles or darkens when concentrate is applied, **DO NOT** use this product on that surface
- **NOT** recommended on glass

SPECIFICATIONS

Appearance: Clear, pink liquid

Odor: None

Density (lbs/gal)(±0.1 @20°C): 8.65

pH (Conc./1%)(±0.5@20°C): 11.6

Refractive index (±.0020@20°C): 1.3470

Hard water tolerance (as ppm CaCO₃): >5000 ppm

Flashpoint (TCC): None

USDA rating: A-1

Foam generation: Moderate

Stability (40°-120°F): Stable


Freeze/thaw stability: OK, 3 cycles

Shelf life (closed containers, 40°-120°F): 1 year minimum


DIRECTIONS



Wear safety equipment recommended on MSDS. Read all directions and cautions prior to beginning work. Remove loose soil and garbage. Divide floor into workable sections.



Dilute **JEP-14** with water as follows:
Heavy soil: 5:1 (26 oz. per gallon)
Moderate soil: 20:1 (6 oz. per gallon)
Light cleaning: 50:1 (2.5 oz. per gallon).



Apply to surface liberally while scrubbing. Allow to work. If soil is heavy, double scrub with an autoscrubber (First pass, squeegee up; second pass, squeegee down, vac on). Pick up as much solution as possible. If possible, allow floor to dry before traffic resumes on cleaned area.



Wear safety equipment recommended on MSDS, place wet floor signs and read all directions and cautions prior to beginning work.